

View Online at https://aerobasegroup.com/nsn/5935-00-147-2983

| Thread Class: | |
|--|-----|
| 2a and 2b | |
| Thread Direction: | |
| Right-hand | |
| Body Style: | |
| Hood, side opening w/clamp | |
| Overall Length: | |
| 3.391 inches | |
| Overall Height: | |
| 2.234 inches | |
| Overall Width: | |
| 1.625 inches | |
| Cable Entrance Diameter: | |
| 1.188 inches | |
| Threaded Device Type: | |
| Coupling facility | |
| Mating End Quantity: | |
| 1 | |
| Contact Position Arrangement Style: | |
| 25-104 single mating end | |
| Polarization Method: | |
| Jackscrew | |
| Shell Type: | |
| Hood, side opening | |
| Connector Locking Method: | |
| Jackscrew-socket | |
| Connector Cable Strain Relief Method: | |
| Cable clamp | |
| Thread Size: | |
| 0.164 inches and 0.164 inches | |
| Insert Material: | |
| Plastic diallyl phthalate single mating end | |
| Shell Material: | |
| Aluminum alloy | |
| Shell Surface Treatment: | |
| Anodize | |
| Insert Material Specification: | |
| Mil-m-14, ty sdg-f military specification single material response single mating e | end |
| Thread Series Designator: | |
| Unc and unc | |
| Reference Number Differentiating Characteristics: | |

Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications

Electrical Plug Connector Body - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.