NSN 5935-00-147-7190

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-147-7190

view Offiline at https://derobasegroup.com/nsi//3335-00-147-7130
Body Style:
Straight shape, external coupling
Overall Length:
0.697 inches
Overall Height:
1.234 inches
Overall Width:
1.234 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.130 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.969 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.969 inches
Distance From Mounting Shoulder To Front Face:
Between 0.442 inches and 0.447 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
16-26 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
18.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:

Aluminum alloy

NSN 5935-00-147-7190

A039b0

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
ncluded Contact Quantity:
26 single mating end single contact grouping
ncluded Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.026 gold grains, troy and 0.026 silver grains, troy
Precious Material:
Gold and silver
Test Data Document:
31349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-c-38999 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
-: