Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-147-9557

## **Body Style:**

Straight shape, external coupling

## **Overall Length:**

0.697 inches

# **Overall Height:**

1.234 inches

# **Overall Width:**

1.234 inches

#### **Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

## **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.130 inches

## Center To Center Distance Between Mounting Facilities Parallel To Height:

0.485 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.485 inches

## Distance From Mounting Shoulder To Front Face:

Between 0.442 inches and 0.447 inches

## Mating End Quantity:

1

## **Contact Position Arrangement Style:**

16-26 single mating end

## **Contact Removability:**

Removable single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

## **Insert Position In Deg:**

30.0

## Shell Type:

Solid

## **Connector Locking Method:**

Bayonet pin

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

# **Terminal Type:**

Crimp single mating end single contact grouping

# Shell Material:

Aluminum alloy



# **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 26 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.026 gold grains, troy and 0.026 silver grains, troy **Precious Material:** Gold and silver **Test Data Document:** 81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-c-38999 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-dtl-38999 spec.

---