Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-149-0735

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling w/backshell
Overall Length:
1.438 inches
Overall Diameter:
1.125 inches
Threaded Device Type:
Back shell
Mating End Quantity:
Contact Position Arrangement Style:
14s-2 single mating end
Contact Removability:
-
Nonremovable single mating end all contact groupings Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Shell Type: Solid Connector Locking Method:
Shell Type: Solid Connector Locking Method: Bayonet latch
Shell Type: Solid Connector Locking Method:
Shell Type: Solid Connector Locking Method: Bayonet latch Thready Qty Per Inch (tpi): 20
Shell Type: Solid Connector Locking Method: Bayonet latch Thready Qty Per Inch (tpi):
Shell Type: Solid Connector Locking Method: Bayonet latch Thready Qty Per Inch (tpi): 20
Shell Type: Solid Connector Locking Method: Bayonet latch Thready Qty Per Inch (tpi): 20 Thread Size:
Shell Type: Solid Connector Locking Method: Bayonet latch Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches
Shell Type: Solid Connector Locking Method: Bayonet latch Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Terminal Location:
Shell Type: Solid Connector Locking Method: Bayonet latch Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Terminal Location: Back single mating end all contact groupings
Shell Type: Solid Connector Locking Method: Bayonet latch Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Terminal Location: Back single mating end all contact groupings Contact Material:
Shell Type: Solid Connector Locking Method: Bayonet latch Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Terminal Location: Back single mating end all contact groupings Contact Material:
Shell Type: Solid Connector Locking Method: Bayonet latch Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end 1st contact grouping
Shell Type: Solid Connector Locking Method: Bayonet latch Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Cortact Size: Back single mating end all contact groupings Contact Material: Copper alloy single mating end 1st contact grouping Insert Material: Plastic diallyl phthalate single mating end
Shell Type: Solid Connector Locking Method: Bayonet latch Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Terminal Location: Back single mating end all contact groupings Contact Material: Copper alloy single mating end 1st contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type:
Shell Type: Solid Connector Locking Method: Bayonet latch Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Cortact Size: Back single mating end all contact groupings Contact Material: Copper alloy single mating end 1st contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings
Shell Type: Solid Connector Locking Method: Bayonet latch Thready Qty Per Inch (tpi): 20 Thread Size: 0.750 inches Cortact Size: Back single mating end all contact groupings Contact Material: Copper alloy single mating end 1st contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Solder well single mating end all contact groupings

## NSN 5935-00-149-0735

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment Specification: Qq-p-416 type 2, cl 3 military specification single treatment response **Included Contact Quantity:** 3 single mating end 1st contact grouping Included Contact Type: Round socket single mating end all contact groupings **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): spec.