Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-149-3195

| Thread Class: |
|---|
| 2a |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 1.625 inches |
| Overall Height: |
| 1.375 inches |
| Overall Width: |
| 1.375 inches |
| Environmental Protection: |
| Salt water resistant |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.062 inches |
| Distance From Mounting Shoulder To Front Face: |
| 0.750 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 35.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 2100.0 single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: |
| 3000.0 single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Externally threaded shell |
| Thread Length: |
| 0.625 inches |
| Thread Size: |
| 1.125 inches |
| Shell Surface Treatment: |
| Cadmium |



Included Contact Quantity:

1 single mating end single contact grouping

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0