## NSN 5935-00-149-3476

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-149-3476 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape w/cable clamp **Overall Length:** 1.125 inches **Overall Height:** 0.688 inches **Overall Width:** 0.688 inches **Unthreaded Mounting Hole Diameter:** 0.099 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 0.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.500 inches **Cable Entrance Diameter:** 0.257 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet latch **Connector Cable Strain Relief Method:** Cable clamp Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 56

**Thread Size:** 

3.000 inches

## NSN 5935-00-149-3476

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back all mating ends all contact groupings
Contact Material:
Copper alloy all mating ends all contact groupings
Contact Surface Treatment:
Silver all mating ends all contact groupings
Insert Material:
Plastic polytetrafluoroethylene single mating end
Terminal Type:
Solder well all mating ends all contact groupings
Shell Material:
Copper alloy
Shell Surface Treatment:
Silver
Included Contact Quantity:
1 single mating end single contact grouping
Precious Material And Location:
Contact @and body surface silver
Precious Material:
Silver
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0