

View Online at <https://aerobasegroup.com/nsn/5935-00-149-4010>

Environmental Protection:

Moisture resistant

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end 2nd contact grouping

Contact Maximum Current Rating In Amps:

20.0 single mating end 2nd contact grouping

Contact Maximum Ac Voltage Rating In Volts:

250.0 single mating end 2nd contact grouping

Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end 1st contact grouping

Polarization Method:

Contact

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end 2nd contact grouping

Insert Material:

Plastic single mating end

Terminal Type:

Screw single mating end 2nd contact grouping

Shell Material:

Iron

Included Contact Quantity:

3 single mating end 2nd contact grouping

Test Data Document:

81348-wc596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0