

View Online at <https://aerobasegroup.com/nsn/5935-00-149-4010>

**Environmental Protection:**

Moisture resistant

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end 2nd contact grouping

**Contact Maximum Current Rating In Amps:**

20.0 single mating end 2nd contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

250.0 single mating end 2nd contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

250.0 single mating end 1st contact grouping

**Polarization Method:**

Contact

**Connector Cable Strain Relief Method:**

Cable clamp

**Terminal Location:**

Back single mating end 2nd contact grouping

**Insert Material:**

Plastic single mating end

**Terminal Type:**

Screw single mating end 2nd contact grouping

**Shell Material:**

Iron

**Included Contact Quantity:**

3 single mating end 2nd contact grouping

**Test Data Document:**

81348-wc596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0