NSN 5935-00-150-1677

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-00-150-1677 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.938 inches **Overall Height:** 1.375 inches **Overall Width:** 1.375 inches **Environmental Protection:** Moisture resistant and vibration resistant and watertight **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches **Distance From Mounting Shoulder To Front Face:** 0.750 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 18-1 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end 1st contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end 1st contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type:

Solid

NSN 5935-00-150-1677

Electrical Receptacle Connector - Page 2 of 3



Connector Locking Method:
Externally threaded shell
Thread Length:
0.625 inches
Thread Size:
1.125 inches
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, class 1 military specification single treatment response single mating end all contact groupings
Terminal Type:
Solder well single mating end all contact groupings
Contact Material Specification:
Qq-b-626, comp 22 federal specification single material response single mating end all contact groupings
Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Cadmium and chromate
Shell Material Specification:
Qq-a-367, comp 6061 federal specification single material response
Insert Material Specification:
Mil-m-14, type mdg military specification single material response single mating end
Included Contact Quantity:
6 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.010 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:

NSN 5935-00-150-1677

Electrical Receptacle Connector - Page 3 of 3



Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.