Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-152-7601



# **Thread Class:** 2b **Thread Direction: Right-hand Body Style:** Straight shape, internal coupling w/strain relief **Body Length:** Between 3.032 inches and 3.124 inches **Overall Diameter:** Between 2.859 inches and 2.891 inches **Cable Entrance Diameter:** Between 1.047 inches and 1.079 inches **Threaded Device Type:** Coupling facility Mating End Quantity: **Contact Position Arrangement Style:** Lk110 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring **Connector Cable Strain Relief Method:** Cable clamp **Thread Length:** 0.500 inches Thready Qty Per Inch (tpi): **Thread Size:** 2.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:**

Copper alloy single mating end single contact grouping

1

6

# NSN 5935-00-152-7601

Electrical Plug Connector - Page 2 of 2



#### **Contact Surface Treatment:**

Silver single mating end single contact grouping

#### **Insert Material:**

Plastic polytetrafluoroethylene single mating end and plastic phenolic single mating end

#### **Terminal Type:**

Solder well single mating end single contact grouping

#### Shell Material:

Aluminum alloy

#### Shell Surface Treatment:

Cadmium

### **Included Contact Quantity:**

110 single mating end single contact grouping

#### Included Contact Type:

Round socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces silver

#### **Precious Material:**

Silver

#### **Thread Series Designator:**

Un

## Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

#### Fiig:

A039b0