

View Online at <https://aerobasegroup.com/nsn/5935-00-153-4358>

Body Style:

Angle shape, internal coupling

Overall Length:

1.750 inches

Overall Height:

1.375 inches

Overall Diameter:

1.375 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

18-32 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

138.0

Shell Type:

Potting

Connector Locking Method:

Bayonet latch

Connector Cable Strain Relief Method:

Potting type

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Rubber single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Insert Material Specification:

Mil-r-3065 military specification single material response single mating end

Included Contact Quantity:

32 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-r-3065 spec.