## NSN 5935-00-153-4369

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-153-4369
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, cl 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Insert Material Specification:
Mil-m-14, ty sdg military specification single material response single mating end
Included Contact Quantity:
40 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.040 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

## NSN 5935-00-153-4369

Electrical Receptacle Connector - Page 2 of 2



Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.