

View Online at <https://aerobasegroup.com/nsn/5935-00-153-6977>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape w/cable clamp

**Overall Length:**

Between 1.078 inches and 1.110 inches

**Bushing Diameter:**

Between 0.422 inches and 0.454 inches

**Overall Height:**

Between 0.672 inches and 0.704 inches

**Overall Width:**

Between 0.672 inches and 0.704 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.484 inches and 0.516 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.484 inches and 0.516 inches

**Cable Entrance Diameter:**

0.188 inches

**Distance From Mounting Shoulder To Front Face:**

0.500 inches

**Threaded Device Type:**

Mounting hole

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Bnc single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Connector Cable Strain Relief Method:**

Compression nut

**Thready Qty Per Inch (tpi):**

56

**Thread Size:**

0.099 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic polyamide single mating end

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0