Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-154-0298

| view online at https://acrobasegroup.com/hsi//0000-00-104-0200 |
|---|
| Thread Class: |
| 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Angle shape, internal coupling |
| Overall Length: |
| 1.507 inches |
| Overall Diameter: |
| 1.010 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 12-8 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 0.0 |
| Shell Type: |
| Potting |
| Connector Locking Method: |
| Internally threaded coupling ring |
| Connector Cable Strain Relief Method: |
| Potting type |
| Thread Size: |
| 0.688 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Rubber single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping |
| |
| Terminal Type: |

Solder well single mating end single contact grouping

NSN 5935-00-154-0298

Electrical Plug Connector - Page 2 of 2



Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and chromate **Included Contact Quantity:** 8 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.