NSN 5935-00-156-0253

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-156-0253

Body Style:
Straight type
Overall Length:
4.790 inches

0.745 inches

Overall Width:

Overall Height:

0.400 inches

Environmental Protection:

Humidity resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.130 inches

Distance Between Mounting Facility Centers:

4.530 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c 3rd treatment response federal specification single mating end single contact grouping and mil-c-14550 3rd treatment response federal standard single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-b-750 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end or mil-p-19833, ty gdi-30f military specification single material response single mating end

Included Contact Quantity:

41 single mating end single contact grouping

Included Contact Type:

Flat socket single mating and single contact grouping

NSN 5935-00-156-0253

Mil-m-14 spec.

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.041 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-dtl-21097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-dtl-21097/13 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):