

View Online at <https://aerobasegroup.com/nsn/5935-00-156-3256>

Thread Class:

2a and 2a

Thread Pitch Diameters:

+0.125 to 0.250 inches

Thread Direction:

Left-hand and left-hand

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

2.328 inches

Overall Height:

2.250 inches

Overall Width:

2.250 inches

Environmental Protection:

Corrosion resistant and pressure proof and vibration resistant and waterproof

Unthreaded Mounting Hole Diameter:

0.203 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.688 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.688 inches

Distance From Mounting Shoulder To Front Face:

1.000 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

16-345 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

73.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1250.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

324.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

1.000 inches and 0.406 inches

Thread Qty Per Inch (tpi):

18 and 8

Thread Size:

1.613 inches and 2.000 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic phenolic single mating end

Terminal Type:

Crimp and solder single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Included Contact Quantity:

5 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.025 gold grains, troy and 0.025 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Npt and special acme

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0