Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-156-6318

Tł	nread Class:
2a	à
Tł	nread Direction:
Ri	ght-hand
В	ody Style:
St	raight shape, external coupling
0	verall Length:
Be	etween 1.486 inches and 1.551 inches
0	verall Height:
Be	etween 1.695 inches and 1.711 inches
0	verall Width:
Be	etween 1.695 inches and 1.711 inches
Er	nvironmental Protection:
Pr	ressure proof and heat resistant and vibration resistant
Uı	nthreaded Mounting Hole Diameter:
0.	116 inches
Ce	enter To Center Distance Between Mounting Facilities Parallel To Height:
Be	etween 1.370 inches and 1.380 inches
Di	stance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Be	etween 1.370 inches and 1.380 inches
Di	stance From Mounting Shoulder To Front Face:
Be	etween 0.894 inches and 0.906 inches
Tł	nreaded Device Type:
Ba	ack shell
M	ating End Quantity:
1	
С	ontact Position Arrangement Style:
24	I-19 single mating end
С	ontact Removability:
Re	emovable single mating end single contact grouping
Po	olarization Method:
Ke	ey, multiple key groove
In	sert Position In Deg:
22	25.0 and 190.0 and 160.0 and 50.0
Sł	nell Type:
So	blid
Co	onnector Locking Method:
Ba	ayonet pin
Tł	nready Qty Per Inch (tpi):
28	3
Tł	nread Size:
1.	500 inches



erminal Location:	
ack single mating end single contact grouping	
ontact Material:	
opper alloy single mating end single contact grouping	
ontact Surface Treatment:	
old single mating end single contact grouping	
ontact Surface Treatment Specification:	
I-g-45204, type 1, class 1 military specification single treatment response single mating end single contact grouping	
erminal Type:	
imp single mating end single contact grouping	
nell Material:	
uminum alloy	
nell Surface Treatment:	
admium	
nell Surface Treatment Specification:	
q-p-416, type 2, cl 3 federal specification single treatment response	
nell Material Specification:	
q-a-367, comp 6061 federal specification single material response	
cluded Contact Quantity:	
single mating end single contact grouping	
cluded Contact Type:	
ound socket single mating end single contact grouping	
ecious Material And Location:	
ontact surfaces gold	
ecious Material And Weight:	
019 gold grains, troy	
ecious Material:	
bld	
est Data Document:	
349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in	n specification
rmat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data or	n certain
vironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
nread Series Designator:	
1	
pecification Data:	
349-mil-c-81511/21 government specification	
nelf Life:	
a	
nit Of Measure:	
emilitarization:	
ig:	
03960	
il-std (military Standard):	