## NSN 5935-00-158-9402

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-158-9402

Body Style:
Straight shape, external coupling w/backshell
Overall Length:
1.492 inches
Overall Height:
1.047 inches
Overall Width:
1.047 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.812 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.812 inches
Distance From Mounting Shoulder To Front Face:
Between 0.431 inches and 0.462 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
12-8 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:

Aluminum alloy

## NSN 5935-00-158-9402

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Included Contact Quantity:
8 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
n order to complete the connector assembly, the user must obtain/provide the backshell
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No
Fiig:
A039b0