NSN 5935-00-159-6808

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-159-6808 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.437 inches **Overall Diameter:** 0.687 inches **Cable Entrance Diameter:** 0.438 inches **Distance From Mounting Shoulder To Front Face:** 0.675 inches **Mounting Facility Thickness:** 0.188 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Uhf single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 120.0 Shell Type: Solid **Connector Locking Method:** Bayonet shell **Connector Cable Strain Relief Method:** Compression nut **Thread Size:** 0.500 inches **Terminal Location:** Copper alloy single mating end single contact grouping

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grou

Contact Surface Treatment:

Gold single mating end single contact grouping

NSN 5935-00-159-6808

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Triaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0