NSN 5935-00-162-1560

Electrical Receptacle Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-00-162-1560 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight edge type w/mounting flange **Overall Length:** 3.500 inches **Overall Height:** 1.210 inches **Overall Width:** 0.370 inches **Distance Between Mounting Facility Centers:** Between 3.193 inches and 3.207 inches **Board Accommodated Length:** 2.700 inches single board **Threaded Device Type:** Mounting hole **Board Accommodated Width:** Between 0.054 inches and 0.071 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of independent contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Contact to contact polarizing keys **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end

Terminal Type:

Wire wrap single mating end single contact grouping

NSN 5935-00-162-1560

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-19833, type gdi-30-f military specification single material response single mating end

Included Contact Quantity:

52 single mating end single contact grouping

Included Contact Type:

Leaf spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.052 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.