## NSN 5935-00-162-4030

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-162-4030 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.062 inches **Bushing Diameter:** 0.438 inches **Overall Height:** 0.690 inches **Overall Width:** 0.690 inches **Unthreaded Mounting Hole Diameter:** 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.500 inches **Distance From Mounting Shoulder To Front Face:** 0.640 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.375 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

## NSN 5935-00-162-4030

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic polyamide single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Chromate
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0