

View Online at <https://aerobasegroup.com/nsn/5935-00-162-5481>

Thread Class:

2b and 2b and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

T-shape

Overall Length:

1.625 inches

Overall Height:

1.218 inches

Overall Width:

0.625 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

3

Contact Position Arrangement Style:

Uhf all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut and internally threaded coupling nut and externally threaded shell

Thread Size:

0.750 inches and 0.750 inches and 0.750 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping and silver all mating ends single contact grouping

Insert Material:

Plastic acrylonitrile-butadiene-styrene (abs) all mating ends

Shell Surface Treatment:

Gold and silver

Included Contact Quantity:

2 all mating ends single contact grouping

Precious Material And Location:

Contact and shell surfaces gold and contact and shell surfaces silver

Precious Material And Weight:

0.130 gold grains, troy and 0.130 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unef and unef and unef

Specification Or Standard:

Ug196/u type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0