

View Online at <https://aerobasegroup.com/nsn/5935-00-163-3401>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Angle shape, external coupling

Overall Length:

0.708 inches

Bushing Diameter:

0.1627 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.340 inches

Overall Height:

0.695 inches

Overall Width:

0.500 inches

Environmental Protection:

Corrosion resistant and vibration resistant and moisture resistant and thermal shock resistant

Unthreaded Mounting Hole Diameter:

Between 0.100 inches and 0.106 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.340 inches

Distance From Mounting Shoulder To Rear Face:

0.190 inches

Flange Length:

0.500 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Sma single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, cl 1, gr c military specification 1st treatment response single mating end single contact grouping and mil-c-14550, cl 2 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping

Shell Material:

Steel comp 303

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Qq-n-290, cl 2 federal specification single treatment response

Shell Material Specification:

Qq-s-764 federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

N/A

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.