NSN 5935-00-163-3835

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-163-3835

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.438 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
N single mating end
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Connector Cable Strain Relief Method:
Cable clamp
Cable clamp Radio Frequency Type Contact Characteristic Impedance In Ohms:
·
Radio Frequency Type Contact Characteristic Impedance In Ohms:
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size:
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.625 inches
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.625 inches Terminal Location:
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.625 inches Terminal Location: Back single mating end single contact grouping
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.625 inches Terminal Location: Back single mating end single contact grouping Contact Material:
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.625 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.625 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.625 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.625 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Insert Material:
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.625 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Insert Material: Plastic tetrafluoroethylene single mating end
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.625 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Insert Material: Plastic tetrafluoroethylene single mating end Terminal Type:
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.625 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Insert Material: Plastic tetrafluoroethylene single mating end Terminal Type: Crimp single mating end single contact grouping
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.625 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Insert Material: Plastic tetrafluoroethylene single mating end Terminal Type: Crimp single mating end single contact grouping Shell Surface Treatment:
Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thread Size: 0.625 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Insert Material: Plastic tetrafluoroethylene single mating end Terminal Type: Crimp single mating end single contact grouping Shell Surface Treatment: Silver

Included Contact Type:

Coaxial socket single mating end single contact grouping

NSN 5935-00-163-3835

Electrical Plug Connector - Page 2 of 2



Precious Material And Location: Contact surfaces and shell surfaces silver Precious Material And Weight: 0.105 silver grains, troy Precious Material: Silver Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: --Demilitarization:

No Fiig: A039b0