

View Online at <https://aerobasegroup.com/nsn/5935-00-163-4535>

**Body Style:**

Straight shape, internal coupling w/strain relief

**Body Length:**

2.219 inches

**Overall Diameter:**

1.500 inches

**Environmental Protection:**

Pressure proof and heat resistant and moisture resistant and vibration resistant and humidity resistant and salt water resistant

**Cable Entrance Diameter:**

0.625 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

37p single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Ball

**Connector Cable Strain Relief Method:**

Cable clamp

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Rubber single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Included Contact Quantity:**

37 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surface gold and contact surface silver

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0