

View Online at <https://aerobasegroup.com/nsn/5935-00-163-7042>

**Body Style:**

Straight shape, internal coupling w/strain relief

**Cable Entrance Diameter:**

Between 0.500 inches and 0.625 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Nonstd single mating end

**Contact Removability:**

Nonremovable single mating end 2nd contact grouping

**Contact Maximum Current Rating In Amps:**

30.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

460.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

250.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Latch

**Connector Cable Strain Relief Method:**

Cord grip

**Terminal Location:**

Back single mating end single contact grouping

**Insert Material:**

Plastic phenolic single mating end

**Terminal Type:**

Screw single mating end single contact grouping

**Shell Material:**

Metal ferrous

**Included Contact Quantity:**

2 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0