## NSN 5935-00-164-9656

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-164-9656

| Thread Class:  |
|--|
| 2a and 2a and 2a   |
| Thread Direction:  |
| Right-hand and right-hand and right-hand   |
| Body Style:  |
| Straight shape   |
| Overall Length:  |
| 1.250 inches   |
| Overall Height:  |
| 0.734 inches   |
| Overall Width:   |
| 0.390 inches   |
| Distance Between Mounting Facility Centers:  |
| 1.032 inches   |
| Threaded Device Type:  |
| Coupling facility and mounting stud  |
| Mating End Quantity:   |
| 1  |
| Contact Position Arrangement Style:  |
| 34 single mating end   |
| Polarization Method:   |
| Jackscrew and polarization boss  |
| Connector Locking Method:  |
| Jackscrew-socket   |
| Thready Qty Per Inch (tpi):  |
| 48 and 48 and 56   |
| Thread Size:   |
| 0.099 inches and 0.099 inches and 0.086 inches   |
| Insert Material:   |
| Plastic diallyl phthalate glass filled single mating end or plastic epoxy single mating end or plastic phenolic single mating end          |
| Insert Material Specification:   |
| Mil-m-14, type sdg-f military specification single material response single mating end or mil-p-19833, type gdi-30f military specification |
| single material response single mating end   |
| Thread Series Designator:  |
| Unc and unc and unc  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A039b0   |

## NSN 5935-00-164-9656

Electrical Receptacle Connector Body - Page 2 of 2



Mil-std (military Standard):

Mil-m-14 spec.