Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-164-9710

Thread Close
Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling w/backshell
Overall Length:
1.870 inches
Overall Height:
1.380 inches
Overall Width:
1.380 inches
Environmental Protection:
Vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.130 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.057 inches and 1.067 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.057 inches and 1.067 inches
Distance From Mounting Shoulder To Front Face:
Between 0.562 inches and 0.593 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
18-4 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thread Size:
1.125 inches

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy 360 single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping and copper single mating end single contact grouping	
Insert Material:	
Rubber synthetic single mating end	
Terminal Type:	
Solder well single mating end single contact grouping	
Contact Material Specification:	
Qq-b-626, comp 360 federal specification single material response single mating end single contact grou	ping
Shell Material:	
Aluminum alloy a380.0	
Shell Surface Treatment:	
Cadmium and chromate	
Shell Material Specification:	
Qq-a-591, alloy a380 federal specification single material response	
Included Contact Quantity:	
4 single mating end single contact grouping	
Included Contact Type:	
Round pin single mating end single contact grouping	
Precious Material And Location:	
Contact surface gold	
Precious Material And Weight:	
0.004 gold grains, troy	
Precious Material:	
Gold	
Thread Series Designator:	
Unef	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Νο	
Fiig:	
A039b0	