NSN 5935-00-164-9712

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-164-9712

Body Style:

Straight shape

Overall Length:

Between 2.714 inches and 2.744 inches

Overall Height:

0.660 inches

Overall Width:

Between 0.479 inches and 0.509 inches

Environmental Protection:

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.086 inches and 0.091 inches

Distance Between Mounting Facility Centers:

Between 2.495 inches and 2.505 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

"b, 17w2" single mating end

Contact Removability:

Nonremovable single mating end 2nd contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end 2nd contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Connector Locking Method:

Friction

Operating Tempurature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Features Provided:

Pre-tinned terminal

Terminal Location:

Back single mating end 2nd contact grouping

Contact Material:

Copper alloy single mating end 2nd contact grouping

Contact Surface Treatment:

Gold and copper single mating end 2nd contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type ii, grade c, class 1 military specification 1st treatment response and mil-c-14550 military specification 2nd treatment response single mating end 2nd contact grouping

NSN 5935-00-164-9712

Electrical Receptacle Connector - Page 2 of 2



Terminal Type: Solder well single mating end 2nd contact grouping Shell Material: Steel Shell Surface Treatment: Cadmium and chromate Shell Surface Treatment Specification: Qq-p-416, type ii, class 2 federal specification all treatment responses Insert Material Specification: Mil-p-19833, type gdi-30f military specification single material response or mil-m-14f, type sdg-f military specification single material response single mating end Included Contact Quantity:
Shell Material: Steel Shell Surface Treatment: Cadmium and chromate Shell Surface Treatment Specification: Qq-p-416, type ii, class 2 federal specification all treatment responses Insert Material Specification: Mil-p-19833, type gdi-30f military specification single material response or mil-m-14f, type sdg-f military specification single material response single mating end Included Contact Quantity:
Shell Surface Treatment: Cadmium and chromate Shell Surface Treatment Specification: Qq-p-416, type ii, class 2 federal specification all treatment responses Insert Material Specification: Mil-p-19833, type gdi-30f military specification single material response or mil-m-14f, type sdg-f military specification single materesponse single mating end Included Contact Quantity:
Shell Surface Treatment: Cadmium and chromate Shell Surface Treatment Specification: Qq-p-416, type ii, class 2 federal specification all treatment responses Insert Material Specification: Mil-p-19833, type gdi-30f military specification single material response or mil-m-14f, type sdg-f military specification single materesponse single mating end Included Contact Quantity:
Cadmium and chromate Shell Surface Treatment Specification: Qq-p-416, type ii, class 2 federal specification all treatment responses Insert Material Specification: Mil-p-19833, type gdi-30f military specification single material response or mil-m-14f, type sdg-f military specification single material response single mating end Included Contact Quantity:
Shell Surface Treatment Specification: Qq-p-416, type ii, class 2 federal specification all treatment responses Insert Material Specification: Mil-p-19833, type gdi-30f military specification single material response or mil-m-14f, type sdg-f military specification single material response single mating end Included Contact Quantity:
Qq-p-416, type ii, class 2 federal specification all treatment responses Insert Material Specification: Mil-p-19833, type gdi-30f military specification single material response or mil-m-14f, type sdg-f military specification single material response single mating end Included Contact Quantity:
Insert Material Specification: Mil-p-19833, type gdi-30f military specification single material response or mil-m-14f, type sdg-f military specification single mater response single mating end Included Contact Quantity:
Mil-p-19833, type gdi-30f military specification single material response or mil-m-14f, type sdg-f military specification single mater response single mating end Included Contact Quantity:
response single mating end Included Contact Quantity:
Included Contact Quantity:
12 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end 2nd contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.012 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.