NSN 5935-00-164-9749

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-164-9749 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.532 inches **Overall Height:** Between 1.610 inches and 1.640 inches **Overall Width:** Between 1.610 inches and 1.640 inches **Unthreaded Mounting Hole Diameter:** Between 0.118 inches and 0.124 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.245 inches and 1.255 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.245 inches and 1.255 inches **Distance From Mounting Shoulder To Front Face:** Between 0.750 inches and 0.760 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 22-19 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 280.0 **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 18

Thread Size:

1.375 inches

NSN 5935-00-164-9749

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Rubber single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
14 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.014 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.