## NSN 5935-00-165-2489

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-165-2489 **Thread Class:** 2a **Body Style:** Straight shape, external coupling **Overall Length:** 1.609 inches **Overall Diameter:** 0.687 inches **Cable Entrance Diameter:** 0.038 inches **Mounting Facility Thickness:** 0.125 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet pin **Connector Cable Strain Relief Method:** Compression nut **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** 

Gold and nickel

**Shell Material Specification:** 

Qq-b-626, comp 22 federal specification single material response

## NSN 5935-00-165-2489

Electrical Receptacle Connector - Page 2 of 2



ln	clu	ded	Conta	ct O	uantity	,-
ш	u	ueu	CUIILA	UL W	uanun	٧.

1 single mating end single contact grouping

**Bushing Accommodation Hole Shape:** 

Round w/flat

**Included Contact Type:** 

Coaxial socket single mating end single contact grouping

**Precious Material And Location:** 

Contact and shell surfaces gold

**Precious Material And Weight:** 

0.105 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0