## NSN 5935-00-165-2511

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-165-2511
Body Style:
Straight shape, external coupling
Overall Length:
1.352 inches
Overall Height:
1.798 inches
Overall Width:
1.798 inches
Environmental Protection:
Moisture resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.436 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.436 inches
Distance From Mounting Shoulder To Front Face:
Between 0.516 inches and 0.546 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
61 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Spring friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Silicon single mating end

## NSN 5935-00-165-2511

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Included Contact Quantity:
61 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.061 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0