

View Online at https://aerobasegroup.com/nsn/5935-00-165-2575

# **Thread Class:**

2a and 2b and 2a

# **Thread Direction:**

Right-hand and right-hand and right-hand

# **Body Style:**

Straight shape

### **Overall Length:**

Between 2.401 inches and 2.411 inches

### **Overall Height:**

Between 0.792 inches and 0.802 inches

### **Overall Width:**

Between 1.245 inches and 1.255 inches

### **Distance Between Mounting Facility Centers:**

Between 1.964 inches and 1.974 inches

### **Threaded Device Type:**

Coupling facility and mounting stud

# Mating End Quantity:

1

# **Contact Position Arrangement Style:**

66 single mating end

# **Polarization Method:**

Jackscrew and polarization boss

#### Shell Type:

Solid

#### **Connector Locking Method:**

Jackscrew-socket

#### **Thread Size:**

0.138 inches and 0.138 inches and 0.112 inches

# **Insert Material:**

Plastic diallyl phthalate single mating end or plastic epoxy single mating end or plastic phenolic single mating end

#### Shell Material:

Aluminum

# Shell Surface Treatment:

Anodize and dichromate potassium

# Shell Surface Treatment Specification:

Mil-a-8625 type 2 military specification single treatment response

### **Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end or mil-p-19833, type gdi-30f military specification

single material response single mating end

# **Thread Series Designator:**

Unc and unc and unc

### Shelf Life:



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.