Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-165-2588

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling w/backshell
Overall Length:
Between 1.460 inches and 1.525 inches
Overall Diameter:
Between 1.330 inches and 1.350 inches
Environmental Protection:
Pressure proof and moisture resistant and vibration resistant
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
16-55 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
49.0 and 169.0 and 200.0 and 244.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Thready Qty Per Inch (tpi):
28
Thread Size:
1.000 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204, type 1, class 2 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping

# NSN 5935-00-165-2588

Electrical Plug Connector - Page 2 of 2



#### Shell Material:

Aluminum alloy

Shell Surface Treatment:

Chromium

Included Contact Quantity:

55 single mating end single contact grouping

# Included Contact Type:

Round socket single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:** 

0.055 gold grains, troy

Precious Material:

Gold

#### **Test Data Document:**

81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Un

Specification Data: 81349-mil-c-81511/26 government specification Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.