

View Online at <https://aerobasegroup.com/nsn/5935-00-166-5851>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Angle shape

Overall Length:

Between 0.720 inches and 0.780 inches

Overall Height:

0.703 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

400.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Spring friction

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene single mating end

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530, comp a federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold

Shell Material Specification:

Qq-c-530, comp a federal specification single material response

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contacts and shell surfaces gold

Precious Material And Weight:

0.105 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0