

View Online at <https://aerobasegroup.com/nsn/5935-00-166-6144>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

Between 1.546 inches and 1.578 inches

Overall Height:

Between 0.843 inches and 0.875 inches

Overall Width:

Between 0.422 inches and 0.454 inches

Distance Between Mounting Facility Centers:

Between 1.243 inches and 1.257 inches

Threaded Device Type:

Mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

20 20-20 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Thread Length:

0.282 inches

Thread Size:

0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sgd-f military specification single material response single mating end

Included Contact Quantity:

20 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.020 gold grains, troy and 0.020 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.