## NSN 5935-00-166-6161

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-166-6161

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
Between 1.542 inches and 1.578 inches
Overall Height:
Between 0.843 inches and 0.875 inches
Overall Width:
Between 0.422 inches and 0.454 inches
Distance Between Mounting Facility Centers:
Between 1.243 inches and 1.257 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
18-62 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Insert Material Specification:
Mil-m-14, type sdg-f military specification single material response single mating end

Included Contact Quantity:20 single mating end single contact grouping

## NSN 5935-00-166-6161

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.020 gold grains, troy and 0.020 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A039b0

Mil-m-14 spec.

Mil-std (military Standard):