## NSN 5935-00-166-6276

Thread Class: 2a and 2b

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-166-6276

2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling w/backshell
Overall Length:
2.175 inches
Overall Diameter:
2.469 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
36-60 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
Insert Position In Deg: 0.0
<del>-</del>
0.0
0.0 Shell Type:
0.0 Shell Type: Solid
0.0 Shell Type: Solid Connector Locking Method:
0.0  Shell Type: Solid  Connector Locking Method: Internally threaded coupling ring
0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Length:
0.0  Shell Type: Solid  Connector Locking Method: Internally threaded coupling ring Thread Length: 0.500 inches and 0.719 inches
O.0  Shell Type: Solid  Connector Locking Method: Internally threaded coupling ring Thread Length: O.500 inches and 0.719 inches Thready Qty Per Inch (tpi):
0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Length: 0.500 inches and 0.719 inches Thready Qty Per Inch (tpi): 18 and 16
O.0  Shell Type: Solid  Connector Locking Method: Internally threaded coupling ring Thread Length: O.500 inches and 0.719 inches Thready Qty Per Inch (tpi): 18 and 16 Thread Size:
0.0  Shell Type: Solid  Connector Locking Method: Internally threaded coupling ring  Thread Length: 0.500 inches and 0.719 inches  Thready Qty Per Inch (tpi): 18 and 16  Thread Size: 2.000 inches and 2.250 inches
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Length: 0.500 inches and 0.719 inches Thready Qty Per Inch (tpi): 18 and 16 Thread Size: 2.000 inches and 2.250 inches Terminal Location:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Length: 0.500 inches and 0.719 inches Thready Qty Per Inch (tpi): 18 and 16 Thread Size: 2.000 inches and 2.250 inches Terminal Location: Back single mating end single contact grouping
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Length: 0.500 inches and 0.719 inches Thready Qty Per Inch (tpi): 18 and 16 Thread Size: 2.000 inches and 2.250 inches Terminal Location: Back single mating end single contact grouping Contact Material:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Length: 0.500 inches and 0.719 inches Thready Qty Per Inch (tpi): 18 and 16 Thread Size: 2.000 inches and 2.250 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end all contact groupings
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Length: 0.500 inches and 0.719 inches Thready Qty Per Inch (tpi): 18 and 16 Thread Size: 2.000 inches and 2.250 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thread Length: 0.500 inches and 0.719 inches Thready Qty Per Inch (tpi): 18 and 16 Thread Size: 2.000 inches and 2.250 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end all contact groupings Contact Surface Treatment: Silver single mating end all contact groupings

## **NSN 5935-00-166-6276**Electrical Plug Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Included Contact Quantity:
7 single mating end 1st contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.047 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Uns and un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0