

View Online at <https://aerobasegroup.com/nsn/5935-00-166-7455>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling strain relief

Overall Length:

3.515 inches

Overall Height:

1.375 inches

Overall Width:

1.375 inches

Environmental Protection:

Moisture resistant and vibration resistant and corrosion resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.063 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.063 inches

Distance From Mounting Shoulder To Front Face:

0.750 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

18-4 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

41.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Cable clamp

Thread Length:

0.625 inches

Thready Qty Per Inch (tpi):

18

Thread Size:

1.125 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Rubber single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surface silver and contact surface gold

Precious Material:

Silver and gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0