

View Online at <https://aerobasegroup.com/nsn/5935-00-167-0241>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

Between 0.865 inches and 0.885 inches

Overall Diameter:

Between 0.365 inches and 0.385 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Mounting Facility Thickness:

0.250 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

Nonstd all mating ends

Contact Removability:

Removable all mating ends single contact grouping

Polarization Method:

Contact

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Size:

0.312 inches and 0.312 inches

Insert Material:

Plastic tetrafluoroethylene all mating ends

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold

Shell Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification single treatment response

Shell Material Specification:

Qq-c-530 federal specification single material response

Included Contact Quantity:

1 all mating ends single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial pin all mating ends single contact grouping

Precious Material And Location:

Shell surface gold

Precious Material And Weight:

0.100 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.