NSN 5935-00-167-6288

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-167-6288

Thread Direction: Right-hand Body Style: Straight shape w/screw locks Overall Length: 4.310 inches Overall Height: 0.531 inches Overall Width: 0.094 inches Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew Connector Locking Method:
Right-hand Body Style: Straight shape w/screw locks Overall Length: 4.310 inches Overall Height: 0.531 inches Overall Width: 0.094 inches Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew
Body Style: Straight shape w/screw locks Overall Length: 4.310 inches Overall Height: 0.531 inches Overall Width: 0.094 inches Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew
Straight shape w/screw locks Overall Length: 4.310 inches Overall Height: 0.531 inches Overall Width: 0.094 inches Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew
Overall Length: 4.310 inches Overall Height: 0.531 inches Overall Width: 0.094 inches Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew
4.310 inches Overall Height: 0.531 inches Overall Width: 0.094 inches Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew
Overall Height: 0.531 inches Overall Width: 0.094 inches Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew
Overall Width: 0.094 inches Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew
Overall Width: 0.094 inches Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew
0.094 inches Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew
Environmental Protection: Moisture resistant and salt water resistant and vibration resistant Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew
Moisture resistant and salt water resistant and vibration resistant Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew
Threaded Device Type: Coupling facility Mating End Quantity: Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew
Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew
Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew
Contact Maximum Current Rating In Amps: 7.5 single mating end single contact grouping Polarization Method: Jackscrew
7.5 single mating end single contact grouping Polarization Method: Jackscrew
Polarization Method: Jackscrew
Jackscrew
Connector Locking Mothod:
Connector Locking Method.
Jackscrew
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping

Included Contact Quantity:

37 single mating end single contact grouping

NSN 5935-00-167-6288Electrical Plug Connector - Page 2 of 2



Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.037 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0