Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-167-7780

### **Body Style:**

Straight edge type w/mounting flange

**Overall Length:** 

4.280 inches

# **Overall Height:**

0.660 inches

## **Overall Width:**

0.343 inches

#### **Environmental Protection:**

Salt water resistant

### **Unthreaded Mounting Hole Diameter:**

#### 0.125 inches

**Distance Between Mounting Facility Centers:** 

Between 4.022 inches and 4.042 inches

#### **Board Accommodated Length:**

3.586 inches single board and 3.606 inches single board

#### **Board Accommodated Width:**

Between 0.054 inches and 0.071 inches

## Mating End Quantity:

1

### **Contact Position Arrangement Style:**

Bridged contacts inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

### **Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

### **Polarization Method:**

Mating end

### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

# Contact Surface Treatment:

Gold single mating end single contact grouping

# **Insert Material:**

Plastic diallyl phthalate single mating end

# **Terminal Type:**

Tab, solder lug single mating end single contact grouping

# Insert Material Specification:

Mil-p-19833, type gdi-30 military specification single material response single mating end

# Included Contact Quantity:

22 single mating end single contact grouping



# Included Contact Type:

Bifurcated accordian leaf spring single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.022 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-p-19833 spec.