NSN 5935-00-167-7783

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-167-7783 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight type **Overall Length:** 7.600 inches **Overall Width:** 0.440 inches **Distance Between Mounting Facility Centers:** 7.302 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of independent contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 800.0 single mating end single contact grouping **Polarization Method:** Contact to contact polarizing keys Thread Length: 0.250 inches **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Unable To Decode:** Unable to decode and unable to decode **Terminal Type:** Tab, solder lug single mating end single contact grouping **Included Contact Quantity:**

86 single mating end single contact grouping

NSN 5935-00-167-7783

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Bifurcated spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.086 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A039b0