## NSN 5935-00-168-1349

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-00-168-1349 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.400 inches **Bushing Diameter:** 0.630 inches **Overall Height:** 1.000 inches **Overall Width:** 1.000 inches **Environmental Protection:** Shock resistant and vibration resistant and salt water resistant **Unthreaded Mounting Hole Diameter:** 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.720 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.720 inches **Cable Entrance Diameter:** 0.500 inches **Distance From Mounting Shoulder To Front Face:** 0.660 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** N single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type:

Solid

**Connector Locking Method:** 

Externally threaded shell

## NSN 5935-00-168-1349

Electrical Receptacle Connector - Page 2 of 3



## **Connector Cable Strain Relief Method:** Compression nut Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.625 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy 360 single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic tetrafluoroethylene single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type ii, class 2 military specification all treatment responses single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Contact Material Specification:** Qq-b-626, 1/2 h federal specification single material response single mating end single contact grouping **Shell Material:** Copper alloy 360 **Shell Surface Treatment:** Silver and chromate **Shell Material Specification:** Qq-b-626, 1/2 h federal specification single material response **Included Contact Quantity:** 1 single mating end single contact grouping **Included Contact Type:** Coaxial pin single mating end single contact grouping **Precious Material And Location:** Contact surface gold and shell surface silver **Precious Material And Weight:** 0.005 gold grains, troy and 0.100 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef Shelf Life: N/a

-

**Unit Of Measure:** 

## NSN 5935-00-168-1349

Electrical Receptacle Connector - Page 3 of 3



Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.