NSN 5935-00-168-4454



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-168-4454 **Body Style:** Straight shape **Overall Length:** 1.330 inches **Overall Height:** 0.385 inches **Overall Width:** 0.208 inches **Environmental Protection:** Vibration resistant and corrosion resistant and heat resistant and cold resistant **Unthreaded Mounting Hole Diameter:** Between 0.089 inches and 0.094 inches **Distance Between Mounting Facility Centers:** 1.115 inches **Mating End Quantity: Contact Position Arrangement Style:** 31 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper alloy single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2 military specification all treatment responses single mating end single contact grouping

Criticality Code Justification:

Feat

Shell Material:

Stainless steel

NSN 5935-00-168-4454

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment: Gold and copper alloy **Shell Surface Treatment Specification:** Mil-f-14072 (e-300) military specification all treatment responses **Shell Material Specification:** Qq-s-766, type 304 condition a federal specification single material response **Insert Material Specification:** Mil-m-14, ty sdg military specification single material response single mating end **Included Contact Quantity:** 31 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Special Features:** Wire leads 1.000 in. Lg **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.031 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.