NSN 5935-00-169-3782

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-169-3782
Body Style:
Straight shape, external coupling w/backshell
Overall Length:
1.328 inches
Overall Height:
1.688 inches
Overall Width:
1.688 inches
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.150 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.297 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.297 inches
Distance From Mounting Shoulder To Front Face:
Between 0.556 inches and 0.587 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
20-16 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1000.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Terminal Type:

Shell Material:

Crimp single mating end single contact grouping

Aluminum alloy

NSN 5935-00-169-3782

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
ncluded Contact Quantity:
16 single mating end single contact grouping
ncluded Contact Type:
Round socket single mating end single contact grouping
Special Features:
Elongated mounting holes 0.120 in. Dia.
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.016 gold grains, troy
Precious Material:
Gold
Test Data Document:
31349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-c-26482 government specification
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
A039b0