Electrical Plug Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-00-169-9421

view Online at https://aerobasegroup.com/nsn/5935-00-16
Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
2.010 inches
Overall Diameter:
2.166 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
28-12 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Thread Length:
0.625 inches
Thready Qty Per Inch (tpi):
18
Thread Size:
1.750 inches
Terminal Location:
Back single mating end single contact grouping

NSN 5935-00-169-9421 Electrical Plug Connector - Page 2 of 2



Cor	oper alloy single mating end single contact grouping
Cor	ntact Surface Treatment:
Silv	er single mating end single contact grouping
Inse	ert Material:
Rub	ober single mating end
Cor	ntact Surface Treatment Specification:
Qq-	s-365 federal specification single treatment response single mating end single contact grouping
Ter	minal Type:
Sol	der well single mating end single contact grouping
She	ell Material:
Alu	minum alloy
She	ell Surface Treatment:
Cac	dmium
She	ell Surface Treatment Specification:
Qq-	-p-416, type 2, cl 3 federal specification single treatment response
Inse	ert Material Specification:
Mil-	r-3065 military specification single material response single mating end
Incl	luded Contact Quantity:
26 క	single mating end single contact grouping
Incl	luded Contact Type:
Rou	und socket single mating end single contact grouping
Pre	cious Material And Location:
Cor	ntact surfaces silver
Pre	cious Material And Weight:
0.02	26 silver grains, troy
Pre	cious Material:
Silv	ver
Thr	read Series Designator:
Uns	3
She	elf Life:
N/a	
Uni	it Of Measure:
Der	militarization:
No	
Fiig	j:
A03	39b0
Mil-	-std (military Standard):