Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-170-1847

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length: Between 0.665 inches and 0.675 inches
Overall Height:
Between 0.495 inches and 0.505 inches
Overall Width:
Between 0.495 inches and 0.505 inches
Unthreaded Mounting Hole Diameter:
Between 0.097 inches and 0.107 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.335 inches and 0.345 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.335 inches and 0.345 inches
Distance From Mounting Shoulder To Front Face:
0.435 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thready Qty Per Inch (tpi):
36
Thread Size:
0.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping



Contact Surface Treatment: Gold single mating end single contact grouping **Insert Material:** Plastic tetrafluoroethylene single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Contact Material Specification:** Qq-c-530, compa federal specification single material response single mating end single contact grouping Shell Material: Steel **Shell Surface Treatment:** Silver **Shell Material Specification:** Qq-s-763, class 303, condition a federal specification single material response **Included Contact Quantity:** 1 single mating end single contact grouping **Included Contact Type:** Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact surface gold and shell surface silver **Precious Material And Weight:** 0.005 gold grains, troy and 0.100 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Uns Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.