NSN 5935-00-170-5323

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-170-5323 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.191 inches **Overall Height:** 0.875 inches **Overall Width:** 0.875 inches **Environmental Protection:** Moisture resistant and vibration resistant and salt water resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.594 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.594 inches **Distance From Mounting Shoulder To Front Face:** Between 0.562 inches and 0.593 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 8s-1 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0

Shell Type:

Solid

NSN 5935-00-170-5323 Electrical Receptacle Connector - Page 2 of 2



| Connector Locking Method: |
|---------------------------------------------------------------------------------------------------------------------------------------------|
| Externally threaded shell |
| Thread Length: |
| 0.375 inches |
| Thread Size: |
| 0.500 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| nsert Material: |
| Rubber single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Shell Surface Treatment Specification: |
| Qq-p-416, type 2, cl 3 federal specification single treatment response |
| ncluded Contact Quantity: |
| 1 single mating end single contact grouping |
| ncluded Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surface gold |
| Precious Material: |
| Gold |
| Test Data Document: |
| 31349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Jnef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| A039b0 |