## NSN 5935-00-170-9647

Telephone Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-170-9647 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Body Style:** Threaded bushing mounted hermetically sealed **Overall Length:** 1.375 inches **Body Diameter:** Any acceptable **Mounting Bushing Length:** 0.281 inches **Body Length:** Any acceptable **Overall Diameter:** Any acceptable **Bushing Accommodation Hole Shape:** Round **Maximum Voltage Rating In Volts:** 115.0 ac **Accommodated Finger Type:** Two conductor, round tip single finger **Finger Accommodation Diameter:** 0.250 inches single finger **Finger Accommodation Length:** 1.218 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.375 inches **Jack Contact Arrangement Designator: Current Rating In Amps:** 1.0 **Mounting Facility Type And Quantity:** 1 bushing **Thread Size:** 0.375 inches **Terminal Type:** Tab, solder lug

Material:

Steel terminal

## NSN 5935-00-170-9647

Telephone Jack - Page 2 of 2



Material:
Steel terminal
Precious Material And Location:
Contact and contact springand contact and contact spring surfaces silver
Precious Material And Weight:
0.210 silver grains, troy
Precious Material:
Silver
Surface Treatment:
Silver contact
Surface Treatment:
Tin terminal
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A03400